

WALL MOUNTED HEAT PUMPS

13 SEER



Haier

INSPIRED LIVING

STANDARD FEATURES

Easy Clean Design
Auto Restart
3 Fan Settings
Intelligent Air

Sleep Mode
24-Hour On/Off Timer
Child Lock
°F/°C Function on Remote



HEAT PUMP SYSTEM	9,000 BTU	12,000 BTU	18,000 BTU	22,000 BTU
OUTDOOR MODEL	HSU09XHK-W	HSU12XHK-W	HSU18VHK-W	HSU24VHK-W
INDOOR MODEL	HSU09XHK-G	HSU12XHK-G	HSU18VHK-G	HSU24VHK-G
PERFORMANCE/ELECTRICAL RATING				
BTU (Cooling)	9,000	12,000	18,000 / 17,500	22,000 / 21,400
BTU (Heating)	9,500	12,000	18,000 / 17,500	22,000 / 21,400
Voltage/Frequency	115V / 60Hz	115V / 60Hz	230 / 208V / 60Hz	230 / 208V / 60Hz
Amps Cooling	7.1	9.5	7.45 / 8.01	8.9 / 9.6
Amps Heating	7.5	9.7	7.45 / 8.01	8.9 / 9.6
Power Input Cooling (watts)	800	1,080	1,645 / 1,600	2,010 / 1,960
Power Input Heating (watts)	850	1,100	1,645 / 1,600	2,010 / 1,960
Maximum Fuse Size (A)	15	15	25	25
SEER	13	13	13	13
HSPF	7.7	7.7	7.7	7.7
EER	11.0	11.1	10.9	10.9
Outdoor Cooling Operating Range °C (°F)	18~46 (64~115)	18~46 (64~115)	18~46 (64~115)	18~46 (64~115)
Outdoor Heating Operating Range °C (°F)	-10~24 (14~75)	-10~24 (14~75)	-10~24 (14~75)	-10~24 (14~75)
Dehumidification (pts/hr)	2.64	2.99	3.5	4.6
Indoor Air Circulation CFM (High/Med/Low)	295	320	580	760
Indoor Sound Level dB (High/Med/Low)	42 / 37 / 35	43 / 39 / 35	51 / 48.5 / 46	49 / 46 / 43
Outdoor Noise Level dB	52	52	60	62
REFRIGERATION LINES				
Connections	Flare	Flare	Flare	Flare
Liquid O.D. (inches)	1/4	1/4	1/4	3/8
Suction O.D. (inches)	3/8	1/2	1/2	5/8
Factory Charge (Refrigerant/OZ)	R-410A / 33.2	R-410A / 46.8	R-410A / 48.33	R-410A / 88.18
Maximum Line Length (feet)	50	50	83.3	83.3
Maximum Height Difference (feet)	32.8	32.8	50	50
DIMENSIONS (INCHES)				
INDOOR UNIT				
Height	10 7/16	10 7/16	11 3/4	12 1/2
Width	31 5/16	36 15/16	41 3/16	45 3/16
Depth	7 3/8	7 3/8	9 2/16	10 1/4
OUTDOOR UNIT				
Height	21 1/4	25 3/16	28 3/4	33 1/16
Width	30 11/16	30 11/16	33 7/8	37 1/2
Depth	9 5/8	9 5/8	12 1/8	13 1/2

Haier



Authorized dealer

HSUHP13ENGES0615

